Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| sources | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------|------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|
| Supplier's name | e or trade mark: | Xavax | | | |
| Supplier's addre | ess: Produktman | agement, Dresdner | Strasse 9, 86653 Monhe | eim, DE | |
| Model identifie | er: 00111442 33V | V Speziallampe Back | ofen | | |
| Type of light so | urce: | | | | |
| Lighting techno | logy used: | HL | Non-directional or directional: | NDLS | |
| Light source cap-type | | G 9 | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | | MLS | Connected light source (CLS): | No | |
| Colour-tuneable | e light source: | No | Envelope: | - | |
| High luminance | light source: | No | | | |
| Anti-glare shield | d: | No | Dimmable: | Yes | |
| Product parameters | | | | | |
| Parameter | | Value | Parameter | Value | |
| General product parameters: | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 33 | Energy efficiency class | G | |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 460 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | |
| On-mode power (P _{on}), expressed in W | | 33,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 100 | |
| Outer | Height | 43 | Spectral power | See image | |
| dimensions | Width | 14 | distribution in the | in last page | |
| without | Depth | 14 | | Page 1 / 3 | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|----------------------------------------------------------------------------------------------------|--------------------------------------|----------------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,462 0,411 |

(a)'-': not applicable; (b)'-': not applicable;

Spectra

