



Item no. 00112080

LED Bulb, GU10, 5.5W, reflector, warm white

Design	PAR 16
Operating Position	360 °
Can be Dimmed	-
Colour Temperature	3000 K
Power Consumption of an Equivalent Incandescent Lamp	30 W
Nominal Service Life	25000 h
Optimal Ambient Temperature	25 °C
Socket	GU 10
Number of Switching Cycles until Premature Failure (min.)	12500
Diameter	50 mm
Height	55 mm
Dimensions Differ From Those of a Standardized Bulb	-
Energy Efficiency Class	A (Scale from A++ to E, Optimum Value: A++)
Lamp Current	45 mA
Start-Up Time Until 60% of Full Light Output Has Been Reached (max.)	1 s
Operating Voltage	230 V
Weighted Energy Consumption	5.5 kWh/1000h
Nominal Power Consumption	5.5 W
Mains Frequency	50 Hz
Nominal Beam Angle Angle of Radiation	35 °
Nominal Light Output	250 lm
Bulb Serves as Replacement for Standard Bulbs of This Size	PAR 16
Suitable for Accent Lighting	Yes - Beam Angle <90° (φ90°)

Errors and omissions excepted, and subject to technical changes.

As of 3rd February 2015.

www.xavax.eu