## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  |            |                         |  |              |  |  |
|--|------------|-------------------------|--|--------------|--|--|
| Supplier's name or trade mark: Xavax   |            |                         |  |              |  |  |
| Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE   |            |                         |  |              |  |  |
| Model identifier: 00112458   |            |                         |  |              |  |  |
| Type of light so   | urce:      |                         |  |              |  |  |
| Lighting techno  | logy used: | HL                      | Non-directional or directional:  | NDLS         |  |  |
| Light source cap-type  |            | E27                     |  |              |  |  |
| (or other electric interface)  |            |                         |  |              |  |  |
| Mains or non-mains:  |            | MLS                     | Connected light source (CLS):  | No           |  |  |
| Colour-tuneable light source:  |            | No                      | Envelope:  | -            |  |  |
| High luminance   |            | No                      |  |              |  |  |
| Anti-glare shield:   |            | No                      | Dimmable:  | Yes          |  |  |
| Product parameters   |            |                         |  |              |  |  |
| Parameter  |            | Value                   | Parameter  | Value        |  |  |
| General product parameters:  |            |                         |  |              |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |            | 30                      | Energy efficiency class  | G            |  |  |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |            | 405 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700        |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |            | 30,0                    | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |            | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 100          |  |  |
| Outer<br>dimensions  | Height     | 74                      | Spectral power   | See image    |  |  |
|  | Width      | 46                      | distribution in the  | in last page |  |  |
| without  | Depth      | 46                      |  | Page 1 / 3   |  |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) |     | range 250 nm to 800<br>nm, at full-load |                |
|--|-----|---|----------------|
| Claim of equivalent power <sup>(a)</sup>   | Yes | If yes, equivalent power (W)            | 40             |
|  |     | Chromaticity coordinates (x and y)      | 0,459<br>0,410 |

(a)'-': not applicable; (b)'-': not applicable;

## Spectra

