## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Xavax

Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE

## Model identifier: 00112553

## Type of light source:

High luminance light source: Anti-glare shield:	No No	Dimmable:	No
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	MLS	Connected light source (CLS):	No
Light source cap-type (or other electric interface)	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consum mode (kWh/100 up to the neares	00 h), rounded	4	Energy efficiency class	E			
	-	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode p expressed in W	ower (P <sub>on</sub> ),	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked stand for CLS, expres rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer dimensions without	Height	105	Spectral power	See image			
	Width	60	distribution in the	in last page			
	Depth	60	-				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	40			
		Chromaticity coordinates (x and y)	0,461 0,415			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	14	Survival factor	0,90			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,55	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'\_-' : not applicable;

