Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Sources	sources					
Supplier's name or tra	de mark:	Xavax				
Supplier's address: Pro	oduktman	agement, Dresdner	Strasse 9, 86653 Monhe	eim, DE		
Model identifier: 0013	12588					
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type		GU4				
(or other electric interf	ace)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		210 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), expressed in W		2,6	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer Heigh	t	40	Spectral power	See image		
dimensions Width)	34	distribution in the	in last page		
without Depth	1	34		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	22		
		Chromaticity	0,457		
		coordinates (x and y)	0,411		
Parameters for directional light sources:					
Peak luminous intensity (cd)	530	Beam angle in degrees, or the range of beam angles that can be set	36		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	2	Survival factor	0,90		
the lumen maintenance factor	0,80				

(a)'-': not applicable; (b)'-': not applicable;

Spectra

