Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Xavax

Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE

Model identifier: 00112644

Type of light source:

(or other electric interface) Mains or non-mains:	MLS	Connected light	No
Colour tupophla light source:	No	source (CLS):	
Colour-tuneable light source: High luminance light source:	No No	Envelope:	-
Anti-glare shield:	No	Dimmable:	No

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
•.	mption in on- 200 h), rounded est integer	8	Energy efficiency class	F			
indicating if it i in a sphere (3	us flux (фuse), refers to the flux 860º), in a wide in a narrow cone	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode expressed in W	power (P _{on}),	7,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	ndby power (P _{net}) essed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer	Height	114	Spectral power	See image			
dimensions	Width	39	distribution in the	in last page			
without	Depth	39	1	Page 1 / 3			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,462 0,413			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	6	Survival factor	0,90			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,55	Colour consistency in McAdam ellipses	2			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-' : not applicable;

(b)'_-' : not applicable;

