## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Xavax

Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE

## Model identifier: 00112840

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	E27					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

		Flouuct para	neters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consump mode (kWh/1000 up to the nearest i	h), rounded	2	Energy efficiency class	E		
Useful luminous indicating if it refe in a sphere (3609 cone (1209) or in a (909)	ers to the flux <sup>o</sup> ), in a wide	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pov expressed in W	ver (P <sub>on</sub> ),	2,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standb for CLS, expresse rounded to the sec	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer H	leight	77	Spectral power	See image		
	Vidth	45	distribution in the	in last page		
without D	Depth	45				
I	-		1	Page 1 /		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	25			
		Chromaticity coordinates (x and y)	0,464 0,416			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	18	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,4	Stroboscopic effect metric (SVM)	0,3			

(a)'-' : not applicable;

(b)'\_-' : not applicable;

