Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	Xavax		
Supplier's addres	ss: Produktman	agement, Dresdner	Strasse 9, 86653 Monhe	eim, DE
Model identifier	: 00112859			
Type of light sou	rce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		G 9		
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	Yes
		Product para	meters	I
Parameter		Value	Parameter	Value
		General product p	parameters:	1
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P _{on}), expressed in W		3,3	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
	Height	53	Spectral power	See image
dimensions without	Width	17	distribution in the	in last page

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	28			
		Chromaticity	0,467			
		coordinates (x and y)	0,415			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	13	Survival factor	0,90			
the lumen maintenance factor	0,94					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,94	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

Spectrum : High

